

PINBALL TV GAME


A dedicated chip TV game may seem strange in these days of the programmable? It won't when you consider the unique games and the fact that this EX-CLUSIVE ETI PROJECT will only ever be built by 500 people.

THIS TV GAME is a 'dedicated chip' version of a game which has been available on cartridge models for some time - breakout. In addition to this, however, there are four pinball games and two solo 'basketball' type of game which are rare - if not unique. The breakout is highly addictive we warn you - it has amazing potential for stopping all life beyond the paddle control. And as only 500 of the chips are available, the Jones's will have some trouble keeping up! The pinball games are available in both flipper and paddle options - and also a small bat option for inflicting greater frustration upon oneself.

Breakout!

Undoubtedly our favourite game was the breakout. It comes in four options, of which the simplest is the most fun. Each hit knocks a brick out of the wall, until a gap right through is produced, and then the ball can

Breakout untouched



the screen Two other versions provide small bat and only five balls with which to work.


Other Attractions


Rather than iterate every last little detail, we've used screen display photos to show the games and options available around those games. Pinball with a paddle is entertaining - to put it mildly!


Solo basketball requires that you keep the ball bouncing on the bat,




Breakout begun - and badly!







Pinball Two - four options



Pinball One - four options



ELECTRONICS TODAY INTERNATIONAL — NOVEMBER 1979

and then press the enter flipper button to "fire the ball upward to the targets. The longer the ball has been bounced on the bat, the more energy it possesses on firing.

No PSU is shown here, beyond a suggested circuit, because these 9V battery eliminators are available commercially at prices that probably make them cheaper to buy than build. If you must go it alone then this is not critical. All that is required is 9V at about 1.0mA or thereabouts.

Construction

There is no setting up to be done, apart from tuning your TV to channel 36. All the components mount onto the PCB, including the modulators, so building up the game should pose no problems at all. Use sockets for the ICs as the 'capital cost' is low compared to that for a new set of chips!

Mount up all the 'passives' first, then the modulators and Xtal. Test your 5V line before plugging in the ICs if possible. If all is well fit a UHF lead and plug into the aerial socket of the TV set. The signal should appear somewhere around channel 36, at which point the white noise will vanish and the first pinball game appear on the screen. The brightness and contrast may need adjusting to get the best display - use the breakout game for this. All three tones of brick should be clearly distinguished from one another

Pressing game select should step the display through the range of games available, with Reset getting things under way

HOW IT WORKS

As with all LSI based games, there is little outside the games chip package of which to speak. All the video sound and sync signals are generated within IC1. The 2112 RAM is provided to hold the 'game selected' signal and score. This is refreshed by IC1 whenever an increment is added by play. At the end of each game (in breakout and basketball) the final score is loaded for display on the screen during the next game. The pinball game scores would require too pinball game scores would require too much screen space, and too many bits,

to store.

Q1 and associated circuitry regulate the 9V input from the external PSU to a the 9V input from the external PSU to a stable 5V to drive the units' own circuitry. The clock frequency is set by XTAL1, C9, C11, and R14 forming a standard Xtal oscillator. IC3 is a 4019 Quad and/or multiplexer to interface SWI-SW6 with the select lines of IC1. Paddle control RV1 is 'padded' by the 27k resistor to prevent a 'zero resistance' condition between the 5V line ance' condition between the 5V line and

ance' condition between the 5V line and

BUYLINES


NIC Models supply all the components for this project.


A complete kit is available for £28.95 all inclusive. Individual components may be purchased as follows:

PCB and Game Chip:

£19.90 all inc. Modulators: £5.80 pair £3.00 all inc.

Xtal The PCB is copyright NIC models and may not be obtained elsewhere. See ad elsewhere in this issue for ordering details. Likewise the chips (all 500 of them!) are initially single sourced.





PARTS LIST


all ½W 5% 100R RESISTORS R1 R2 R3 R4 3k3 1k0 680R 2k2 10k R4 R5, 6, 15 R7-12 R13 R14 R16 100k 1k5 CAPACITORS CAPACITORS
C1, 6, 7, 13, 14 100p polystyrene
C2, 3 220u 16V electrolytic
C4, 10, 12 100n polyester
C5 10n polyester
C8 470p polystyrene
Ca 4p7 ceramic
Cu 33p ceramic

SEMICONDUCTORS

IC1 IC2 IC3 See text 2112 4019 BC 337 5V1 400mW 01 ZD1

MISCELLANEOUS XTAL (3.57 MHz) Modulators RV1 (250k linear) Box to suit PCB

Internal view of the unit, showing the space left to mount a PSU board should you desire to power it this way.







TOTAL AMPLIFICATION FROM

WE NOW OFFER THE WIDEST RANGE OF SOUND PRODUCTS **POWER SUPPLIES**

Box 12035 S-750 12 Uppsala 12

STEREO PRE-AMPLIFIER







CPR 1 — THE ADVANCED PRE-AMPLIFIER. The best pre-amplifier in the U.K. The superiority of the CPR 1 is probably the disc stage. The overload margin is a superb 40dB, this together with the high slewing rate ensures clean top, even with high output cartridges tracking heavily modulated records, Common-mode distortion is eliminated by an unusual design. R.I.A.A. is accurate to 1 diffs. signal to noise ratio is 70dB relative to 3.5mV, distortion < .005% at 30dB overload 20kHz.

Following this stage is the flat gain/balance stage to bring tape, tuner, etc. up to power amp signal levels. Signal to noise ratio 86dB, slew-rate 3V/uS. T.H.D. 20Hz-20kHz<.008% at any level.

F.E.T. muting. No controls are fitted. There is no provision for tone controls. CPR 1 size is $138\times80\times20$ mm. Supply to be \pm 15 volts.

MC 1 — PRE-PRE-AMPLIFIER. Suitable for nearly all moving-coil cartridges. Sensitivity 70/170uV switchable on the p.c.b. This module brings signals from the now popular low output moving-coil cartridges up to 3.5mV (typical signal required by most pre-amp disc inputs). Can be powered from a 9V battery or from our REG 1 regulator board.

 $\textbf{XO2:XO3} - \textbf{ACTIVE CROSSOVERS}. \ XO2 - two way, \ XO3 = three way. Slope 24dB/octave. Crossover points set to order within 10%.$

REG 1 — POWER SUPPLY. The regulator module, REG 1 provides 15-0-15v to power the CPR 1 and MC 1. It can be used with any of our power amp supplies or our small transformer TR 6. The power amp kit will accommodate it.

POWER AMPLIFIERS. It would be pointless to list in so small a space the number of recording studios, educational and government establishments, etc., who have been using CRIMSON amps satisfactorily for quite some time. We have a reputation for the highest quality at the lowest prices. The power amp is available in five types, they all have the same specification. T.H.D. typically 0.1% any power 1kHz 8 ohms T.I.D. insignificant, slew rate limit 25V/uS, signal to noise ratio 110dB, frequency response 10Hz-35kHz — 3dB stability unconditional, protection drives any load safely, sensitivity 775mV (250mV or 100mV or request), size 120×80×25mm.

POWER SUPPLIES. We produce suitable power supplies which use our superb TOROIDAL transformers only 50mm high with a 120-240 primary and single bolt fixing (includes capacitors/bridge rectifier).

We produce suitable power supplies which use our superb TOROIDAL transformers only 50mm high with a 12D-240 primary and single bolt fixing (includes capacitors/bndge rectifier)

PRE-AMPLIFIER KIT FIRST INCLUDES ALL METAL WORK POTS KNOBS ETC.

TO MAKE A COMPLETE PRE-AMP with CPR 1.SI MODULE AND THE MC1/2/IS REQUIRED.

POWER AMPLIFIER KIT

The kit includes all metalwork, heatsinks and hardware to house any two of our power amp modules plus a po-supply. It is contemporarily styled and its quality is consistent with that of our other products. Comprehent instructions and full back-up service enables a nonze to build it with confidence in a few hours.





£31.65 £40.87 £21.28 £33.17 £38.07

£15.18 £23.58

€1.97

1 using 2×170W €5.75

POWER AMPLIFIER MODULES				POWER AMP KIT
CE 608 80W/8 ohms 35-0.35v CE 1004 100W/4 ohms 35-0.35v CE 1008 100W/8 ohms 45-0.45v CE 1704 170W/4 ohms 45-0.45v CE 1708 170W/8 ohms 60-0-60v			£19.52 £23.02 £25.96 £31.00 £33.97	These are available in two one uses standard comported other (the S), uses Mi where necessary and tantal tors.
TOROIDAL POWER SUPPLIES PS1 for 2xCE 608 or TxCE 1004 CPS2 for 2xCE 1004 or 2/4xCE 608 CPS3 for 2xCE 1008 or 1xCE 1704 CPS4 for 1xCE 1008 CPS5 1 for 1xCE 1708 CPS6 mk 2xCE 1704 or 2xCE 1708			£16.58 £18.80 £19.75 £17.12 £24.15 £25.53	CPR1 CPRIS MC1 MC1 MC1S Pre-amp Kit
HEATSINKS Light duty, 50mm, 2 C/W Medium power, 100mm, 1-4 C/W Disco/group, 150mm, 1-1C/W Fan, 80mm, state 1/20 or 240v Fan mounted on two drilled 100mm	heatsinks		£3.04	ACTIVE CROSSOVERS X02 X03 POWER SUPPLY REGI £6.90 TR6
2x4 C/W, 65 max with two 170W modules THERMAL CUT-OFF, 70°C				DRIDGE DRIVER, BD1 Obtain up to 340W using amps and this module
Distributors.	CP	184	MOS	FIFKTRIK

CRIMSON ELEKTRIK 1A STAMFORD STREET, LEICESTER LE1 6NLL. Tel. (0533) 553508 U.K. — please allow up to 21 days for delivery

Badger Sound Services Ltd., 46 Wood Street, Lytham St. Annes, Lancashire FY8 1QG All prices shown are UK only and include VAT and post COD 90p extra, £100 limit. Export is no problem, pleas write for specific quote. Send large SAE or 3 International Reply Coupons for datailed information.